

Anglapro - CORE STL Series

Standard Model - Punt - V-Nose - Unpainted



SPECIFICATIONS	354	374	394	404
LENGTH (M)	3.6	3.8	3.9	4.1
BEAM (MM)	1480	1650	1740	1890
DEPTH (MM)	740	740	740	830
BOTTOM SIDES (MM)	1.6	1.6	2	3
TOP SIDES (MM)	1.6	1.6	2	3
MAX HP	15	20	25	30
MAX TRANSOM WEIGHT (KG)	68	68	110	110
TRANSOM HEIGHT	LONG 20"	LONG 20"	LONG 20"	LONG 20"
MAX # PEOPLE	3	3	3	3
BASE BOAT HULL WEIGHT (KG)	89	96	135	165
FEATURES	354	374	394	404
ANCHOR TRAY	STD	STD	STD	STD
BILGE PUMP MOUNTING PLATE	STD	STD	STD	STD
BOWEYE (LARGE 2 HOLE)	STD	STD	STD	STD
BUNGS (LARGE 2)	STD	STD	STD	STD
CASTING PLATFORM - OFF FRONT X-THWART WITH 1 HATCH	OPT	OPT	OPT	STD
FLOOR - LOW SUPPORTED (CHARCOAL CARPETED)	OPT	OPT	STD	STD
FLOTATION X-THWART (BASIC)	STD	STD	STD	STD
FUEL TANK RACK - REAR	OPT	OPT	STD	STD
LIFTING HANDLES (2 ON STERN/1 ON BOW)	STD	STD	STD	OPT
MOTOR BOARD - ANTI-ROT	STD	STD	STD	STD
ROWLOCK HOLDERS (2)	STD	STD	STD	N/A
SEATS- X-THWART TYPE (2)	STD	STD	STD	STD
SIDE POCKETS	OPT	OPT	STD	STD
SOLID TRANSOM CORNERS	STD	STD	STD	STD
STEP & GRAB RAIL (REAR)	OPT	OPT	OPT	STD
TRANSDUCER BRACKET (1)	STD	STD	STD	STD
FACTORY OPTIONS AVAILABLE	354	374	394	404
BILGE PUMP 500GPH	OPT	OPT	OPT	OPT
CASTING PLATFORM - OFF FRONT X-THWART WITH 1 HATCH	N/A	OPT	OPT	STD
CASTING PLATFORM - OFF REAR X-THWART WITH 2 HATCHES	N/A	OPT	OPT	OPT
ELECTRIC MOTOR BRACKET	N/A	OPT	OPT	OPT
ELECTRICAL RIGGING (NAV, ANCHOR LIGHTS, 12V SOCKET & 5 GANG SWITCH PANEL)	OPT	OPT	OPT	OPT
GRAB RAILS WITH NAV LIGHT BRACKETS	OPT	OPT	OPT	OPT
PAINTED HULL (1 COLOUR) STANDARD GRAPHICS	OPT	OPT	OPT	OPT
SIDE DECKS FULLY WELDED	N/A	N/A	OPT	OPT
SIDE RAILS - REAR	OPT	OPT	OPT	OPT