

# Anglapro - CORE CSR Series

Standard Model - Open Boat - Unpainted



SPECIFICATIONS	364	384	404	424	444
LENGTH (M)	3.7	3.8	4.1	4.3	4.5
BEAM (MM)	1465	1670	1840	2080	2110
DEPTH (MM)	770	825	925	945	1100
BOTTOM SIDES (MM)	1.6	2	3	3	3
TOP SIDES (MM)	1.6	2	3	3	3
MAX HP	15	25	30	40	50
MAX TRANSOM WEIGHT (KG)	60	90	110	110	130
TRANSOM HEIGHT	SHORT 15"	LONG 20"	LONG 20"	LONG 20"	LONG 20"
MAX # PEOPLE	3	3	4	4	4
BASE BOAT HULL WEIGHT (KG)	100	170	236	265	388
FEATURES	364	384	404	424	444
ANCHOR TRAY	STD	STD	N/A	N/A	N/A
ANCHOR WELL	N/A	N/A	STD	STD	STD
BILGE PUMP MOUNTING PLATE	STD	STD	STD	STD	STD
BOWEYE (LARGE 2 HOLE)	STD	STD	STD	STD	STD
BUNGS (LARGE 2)	STD	STD	STD	STD	STD
CASTING PLATFORM - OFF FRONT X-THWART WITH 1 HATCH	OPT	OPT	STD	STD	STD
FLOOR - LOW SUPPORTED (CHARCOAL CARPETED)	OPT	STD	STD	STD	STD
FLOTATION X-THWART (BASIC)	STD	STD	STD	STD	STD
FUEL TANK RACK	OPT	STD	STD	STD	STD
GRAB RAILS (FRONT) WITH NAV LIGHT BRACKETS	OPT	OPT	STD	STD	STD
GRAB RAILS (SIDE)	OPT	OPT	STD	STD	STD
LIFTING HANDLES (2 ON STERN/1 ON BOW)	STD	STD	STD	STD	STD
MOTOR BOARD - ANTI-ROT	STD	STD	STD	STD	STD
SEAT - X-THWART TYPE (2)	STD	STD	STD	STD	STD
SIDE DECKS FULLY WELDED	N/A	OPT	STD	STD	STD
SIDE POCKETS - LONG	OPT	STD	STD	STD	STD
SOLID TRANSOM CORNERS	STD	STD	N/A	N/A	N/A
STEP & GRAB RAIL (REAR)	N/A	N/A	STD	STD	STD
TRANSDUCER BRACKET (1)	STD	STD	N/A	N/A	N/A
TRANSDUCER BRACKET (2)	OPT	OPT	STD	STD	STD
FACTORY OPTIONS AVAILABLE	364	384	404	424	444
CASTING PLATFORM - REAR	N/A	N/A	OPT	OPT	OPT
CONSOLE - DINGHY STYLE	N/A	N/A	OPT	OPT	OPT
ELECTRIC MOTOR BRACKET	OPT	OPT	OPT	OPT	OPT
ELECTRICAL RIGGING (NAV, ANCHOR LIGHTS, 12V SOCKET & 5 GANG SWITCH PANEL)	OPT	OPT	OPT	OPT	OPT
PAINTED HULL (1 COLOUR) STANDARD GRAPHICS	OPT	OPT	OPT	OPT	OPT
SPRAY CHINE (1500MM)	OPT	OPT	OPT	OPT	OPT