

TRIXSTA

Standard Model - X-OVER - Painted - TILLER STEER



SPECIFICATIONS	41	43
LENGTH (MM)	4160	4500
BEAM (MM)	1840	2040
DEPTH (MM)	925	945
BOTTOM SIDES (MM)	3	3
TOP SIDES (MM)	3	3
MAX HP	30	40
MAX TRANSOM WEIGHT (KG)	110	125
TRANSOM HEIGHT	LONG 20"	LONG 20"
MAX # PEOPLE	4	4
BASE BOAT HULL WEIGHT (KG)	236	262
FEATURES	41	43
ANCHOR TRAY	STD	STD
ANCHORING CLEAT	STD	STD
BATTERY SHELF/RACK - TRANSOM	STD	STD
BILGE PUMP MOUNTING PLATE	STD	STD
BOARD RACKS ON SIDE POCKETS	STD	STD
BOWEYE (LARGE 2 HOLE)	STD	STD
BUNGS (LARGE 2)	STD	STD
CASTING PLATFORM - OFF FRONT X-THWART WITH 1 HATCH	STD	STD
FLOOR - LOW SUPPORTED, CARPETED (CHARCOAL)	STD	STD
FLOTATION X-THWART (BASIC)	STD	STD
FUEL TANK RACK	STD	STD
LIFTING HANDLES (1 ON STERN)	STD	STD
MOTOR BOARD - ANTI-ROT	STD	STD
PAINTED - WHITE	STD	STD
PREMIUM GRAPHICS PACK	STD	STD
ROD HOLDERS x 2 IN SIDE DECKS - MID SHIP	STD	STD
ROPE AND JACKET HOOKS	STD	STD
SEAT - X-THWART TYPE (2) - WITH UPHOLSTERED CUSHIONS	STD	STD
SIDE DECKS FULLY WELDED	STD	STD
SIDE POCKETS - LONG	STD	STD
STANDARD FACTORY TOWER WITH 2 x ROD HOLDERS	STD	STD
STEP & GRAB RAIL (REAR)	x1	x1
TRANSDUCER BRACKET (1)	STD	STD
FACTORY OPTIONS AVAILABLE	41	43
BILGE PUMP 500GPH	OPT	OPT
ELECTRIC MOTOR BRACKET	OPT	OPT
ELECTRICAL RIGGING (NAV, ANCHOR LIGHTS, 12V SOCKET & 5 GANG SWITCH PANEL)	OPT	OPT
GRAB RAILS (FRONT) WITH NAV LIGHT BRACKETS	OPT	OPT
GRAB RAILS (SIDE)	OPT	OPT
PAINT - SIDE COLOURS	OPT	OPT
SPRAY CHINE (1500MM)	OPT	OPT

E.&O.E.2018_2019 Revision 1